

THERMOSTATS & CONTROLLERS

THERMOSTAT GUARDS

ATK, A/LC, BA, TG, TG500, SGP-2 SERIES

DESCRIPTION

The TG, ATK, A/LC, F29 and BAPI-Guard Thermostat Guards are used to enclose and protect wall thermostats and sensors against tampering, damage, and unauthorized adjustment of thermostat settings.

FEATURES

TG500 Series Vented Guards

- Patented, double-wall construction
- Available in various sizes
- Clear plastic or painted steel
- Includes ring base, cover, lock and two keys

BAPI-Guard Series Vented Guards

- Clear low profile design
- All mounting, hardware included
- Key lock for vertical or horizontal mounting
- Two sizes to fit most applications
- Hammer tough

ATK Series

- Available in wire and cast aluminum
- Vertical and horizontal mounting

A/LC Series

- Clear Plastic
- Vented Design

TG Series Vented Guards

- One piece U.V. stabilized high impact molded polycarbonate housing
- Ring base is 16 gauge steel with white finish and four mounting holes
- Stainless steel fasteners secure housing to base
- Ventilation holes allow air to circulate freely

F29 Series

- Clear plastic, opaque, or metal housings
- 18 gauge cover, 22 gauge frame on metal units
- Beige enamel finish available on metal units
- Solid or ring base

SGP-2

- Combination tumbler lock with resettable code
- Reduce your energy consumption
- Control your overhead cost



SGP-201401



A/Locking Cover



BAPI-GUARD



TG510A



TG-1



ATK03



ATK04

ORDERING INFORMATION

Model	Size	Cover	Ring Base	Solid Wall Plate	Inside Dimensions			Outside Dimensions		
					Height in (cm)	Width in (cm)	Depth in (cm)	Height in (cm)	Width in (cm)	Depth in (cm)
TG510A1001	Small	Clear	Clear	Opaque	4.38 (11.13)	4.38 (11.13)	2.25 (5.72)	5.88 (14.94)	5.88 (14.94)	2.5 (6.35)
TG510D1005		Painted Steel (off-white)	Opaque		4.38 (11.13)	4.38 (11.13)	2.25 (5.72)	5.88 (14.94)	5.88 (14.94)	2.5 (6.35)
BA/BG2		Clear	Clear	—	4.8 (12.3)	2.9 (7.4)	1.43 (3.65)	6.75 (17)	4.75 (12)	2.1 (5.4)
ATK03		Wire	—		4.25 (10.80)	2.63 (6.66)	1.63 (4.12)	—	—	—
ATK04		Cast Aluminum			4.25 (10.80)	2.75 (6.98)	1.63 (4.12)	—	—	—
F229-0225	Medium	Clear			3.88 (9.86)	3.5 (8.89)	2.5 (6.35)	—	—	—
TG511A1000		Clear	Clear	Opaque	5.06 (12.85)	6.06 (15.39)	2.63 (6.68)	6.5 (16.51)	7.5 (19.05)	2.94 (7.47)
TG511D1004		Painted Steel (off-white)	Opaque		5.06 (12.85)	6.06 (15.39)	2.63 (6.68)	6.5 (16.51)	7.5 (19.05)	2.94 (7.47)
F29-0227		Clear	—	—	5.25 (13.34)	4.63 (11.76)	3.25 (8.26)	—	—	—
TG-1		Pearlescent	White	—	2.8 (7.1)	5.0 (12.7)	3.1 (7.9)	5.375 (13.7)	7.75 (19.7)	4.25 (10.8)
TG-2	Large	Clear	White		2.8 (7.1)	5.0 (12.7)	3.1 (7.9)	5.375 (13.7)	7.75 (19.7)	4.25 (10.8)
TG-37		Prismatic	White		3.0 (7.6)	5.5 (14.0)	3.1 (7.9)	5.875 (14.9)	8.5 (21.6)	4.125 (10.5)
TG512A1009		Clear	Clear	Opaque	5.88 (14.94)	8.38 (21.29)	3.0 (7.62)	7.25 (18.42)	9.75 (24.77)	3.38 (8.59)
TG512D1003		Painted Steel (off-white)	Opaque		5.88 (14.94)	8.38 (21.29)	3.0 (7.62)	7.25 (18.42)	9.75 (24.77)	3.38 (8.59)
BA/BG		Clear	Clear	—	6.9 (17.5)	4.7 (11.8)	1.75 (4.43)	9.45 (24)	9.45 (24)	3.0 (7.6)
ATK63		Wire	—	—	6.50 (16.51)	6.38 (16.21)	3.0 (7.62)	—	—	—
F29-0231		Clear			7.06 (17.93)	4.13 (10.49)	2.25 (5.72)	—	—	—
F29-0143					6.36 (16.15)	3.5 (8.89)	3.25 (8.26)	—	—	—
F29-0198					8.13 (20.65)	4.63 (11.76)	3.63 (9.22)	—	—	—
F29-0220		Painted Steel (beige)			7.13 (18.11)	4.63 (11.76)	3.25 (8.26)	—	—	—
F29-0222		Mounted			6.63 (16.84)	4.50 (11.43)	3.38 (8.58)	—	—	—
F29-0192		Hinged			6.25 (15.88)	4.75 (12.07)	3.0 (7.62)	—	—	—
F29-0193		Hinged			6.0 (15.24)	3.82 (9.7)	3.13 (7.95)	—	—	—
SGP-201401		Clear	Clear	—	4.5 (11.43)	7.25 (18.42)	2.25 (5.72)	6 (15.24)	9.25 (23.5)	2.625 (6.67)
A/LOCKING-COVER		Clear		Opaque	6.36 (16.15)	5.63 (14.3)	3 (7.62)	6.625 (16.83)	5.9 (14.99)	3.25 (8.26)