

Steel City® Spring Steel Fasteners

Miscellaneous Components





Fig. 1




Fig. 2

Features

- Provides secure positioning of pipe sleeve for concrete pouring of wall and floor forms
- Accommodates up to Schedule 80 pipe wall thicknesses
- Installs easily with a hammer

Pipe Sleeve Positioner

Cat. No.	Fig. No.	Sleeve Dia.	Description / Wall Thickness	Std. Ctn.
SSF-MPS	1	All dia.	Pipe sleeve positioner, 5/16" and under	100
SSF-MPS	1	2"-6"	Pipe sleeve positioner, Schedule 40 Pipe	100
SSF-BF1/2	2	6"	Pipe sleeve positioner, Schedule 80 Pipe	100
SSF-BF1/2	2	8"-10"	Pipe sleeve positioner, Schedule 40 Pipe	100
SSF-BF3/4	2	9"-14"	Pipe sleeve positioner, Schedule 80 Pipe	100





Fig. 1




Fig. 2

Features

- Order s-hooks and jack chain with your Spring Steel orders to save on freight, energy, and purchase orders
- S-hook supports 29 lbs. static load limit

S Hook and Jack Chain

Cat. No.	Fig. No.	Description	Static Load Limit	Std. Ctn.
SH10	1	S-Hook	29	1000
JC50	2	Jack Chain, 50ft.	—	1000
JC100-SC	2	Jack Chain, 100ft.	—	1000